

LIQUEFIED PETROLEUM GAS (LPG)**AL623****Danger****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : LIQUEFIED PETROLEUM GAS (LPG)
SDS Nr : AL623

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
Test gas / Calibration gas. Laboratory use Contact supplier for more uses information

1.3. Details of the supplier of the safety data sheet

Company identification : Air Liquide Australia Limited
Level 9 / 380 St. Kilda Road
Melbourne VIC 3004 Australia
Tel: + 61 3 9697 9888
Fax: + 61 3 9690 7107
ALAEquiries@AirLiquide.com

1.4. Emergency telephone number

Emergency telephone number : 1800 812 588

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture****Hazard Class and Category Code Regulation EC 1272/2008 (CLP)**

• Physical hazards : Flammable gases - Category 1 - Danger - (CLP : Flam. Gas 1) - H220
Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280

Classification EC 67/548 or EC 1999/45

: F+; R12

2.2. Label elements**Labelling Regulation EC 1272/2008 (CLP)**

• Hazard pictograms



• Hazard pictograms code : GHS02 - GHS04

• Signal word : Danger

• Hazard statements : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.

• Precautionary statements

- Prevention : P210 - Keep away from heat, sparks, open flames or hot surfaces. – No smoking.

- Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - Eliminate all ignition sources if safe to do so.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: None.



MATERIAL SAFETY DATA SHEET

Page : 2

Revised edition no : 3

Date : 7 / 11 / 2012

Supersedes : 25 / 9 / 2012

LIQUEFIED PETROLEUM GAS (LPG)

AL623

SECTION 2. Hazards identification (continued)

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Mixture.

Substance name	Contents	CAS No	EC No	Annex No		Classification
Propane	: Between 45 and 55 %	74-98-6	200-827-9	601-003-00-5	* 2	F+; R12 Flam. Gas 1 (H220) Liq. Gas (H280)
Butane n-	: Between 45 and 55 %	106-97-8	203-448-7	601-004-00-0	* 2	F+; R12 Flam. Gas 1 (H220) Liq. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Adverse effects not expected from this product.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- : No effect on living tissue.
Refer to section 11.
Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

- : None.

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : All known extinguishants can be used.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion.
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

5.3. Advice for fire-fighters

- Specific methods : Coordinate fire measure to the surrounding fire. Cool endangered containers with water spray jet from a protected position. Do not empty contaminated fire water into drains.
If possible, stop flow of product.
- Special protective equipment for fire fighters : None.

Air Liquide Australia Limited

Level 9 / 380 St. Kilda Road Melbourne VIC 3004 Australia

Tel: + 61 3 9697 9888

Fax: + 61 3 9690 7107

ALAEquiries@AirLiquide.com

In case of emergency : 1800 812 588

LIQUEFIED PETROLEUM GAS (LPG)

AL623

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.

6.2. Environmental precautions

: None.

6.3. Methods and material for containment and cleaning up

: None.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling**Safe use of the product**

: Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Only experienced and properly instructed persons should handle gases under pressure. The product must be handled in accordance with good industrial hygiene and safety procedures.
Do not smoke while handling product.
Ensure the complete gas system was (or is regularly) checked for leaks before use.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Protect cylinders from physical damage; do not drag, roll, slide or drop.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
Never attempt to repair or modify container valves or safety relief devices.
Damaged valves should be reported immediately to the supplier.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

7.2. Conditions for safe storage, including any incompatibilities

: Keep container below 50°C in a well ventilated place.
Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Containers should be stored in the vertical position and properly secured to prevent toppling.
Stored containers should be periodically checked for general condition and leakage.
Container valve guards or caps should be in place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.

7.3. Specific end use(s)

: None.

LIQUEFIED PETROLEUM GAS (LPG)**AL623****SECTION 8. Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits****Butane n-**

: MAK (AU) Tagesmittelwert (ml/m³) : 800
: MAK (AU) Tagesmittelwert (mg/m³) : 1900
: MAK (AU) Kurzzeitwerte (mg/m³) : 3800
: MAK (AU) Kurzzeitwerte (ml/m³) : 1600
: TLV© -TWA [ppm] : 800
: LTEL - UK [ppm] : 600
: STEL - UK [mg/m³] : 750
: VME - France [mg/m³] : 1900
: VME - France [ppm] : 800
: AGW (8h) - Germany [mg/m³] TRGS 900 : 2400
: AGW (8h) - Germany [ppm] TRGS 900 : 1000
: Exceeding factor AGW - Germany TRGS 900 : 4
: VLA-ED - Spain [ppm] : 1000
: Grænserværdier (DK) (ppm) : 500
: HTP-vården (FI) - 8 H - [ppm] : 800
: HTP-vården (FI) - 8 H - [mg/m³] : 1900
: HTP-vården - 15min - [ppm] : 1000
: Grænserværdier (DK) : 1200
: HTP-vården - 15min - [mg/m³] : 2400
: GV Value Limit (Norway) [ppm] : 250
: GV Value Limit (Norway) [mg/m³] : 600
: TLV-TWA (Belgium) (ppm) : 800

Propane

: MAK (AU) Tagesmittelwert (ml/m³) : 1000
: MAK (AU) Tagesmittelwert (mg/m³) : 1800
: MAK (AU) Kurzzeitwerte (mg/m³) : 3600
: MAK (AU) Kurzzeitwerte (ml/m³) : 2000
: TLV© -TWA [ppm] : 2500
: AGW (8h) - Germany [mg/m³] TRGS 900 : 1000
: AGW (8h) - Germany [ppm] TRGS 900 : 1800
: Exceeding factor AGW - Germany TRGS 900 : 4
: VLA-ED - Spain [ppm] : 1000
: Grænserværdier (DK) (ppm) : 1000
: HTP-vården (FI) - 8 H - [ppm] : 800
: HTP-vården (FI) - 8 H - [mg/m³] : 1500
: HTP-vården - 15min - [ppm] : 1100
: Grænserværdier (DK) : 1800
: HTP-vården - 15min - [mg/m³] : 2000
: GV Value Limit (Norway) [ppm] : 500
: GV Value Limit (Norway) [mg/m³] : 900
: 8-Hour TWA (PL) (NDS) (mg/m³) : 1800

DNEL: Derived no effect level

: None available.
: None available.

PNEC: Predicted no effect concentration

: None available.
: None available.

8.2. Exposure controls**8.2.1. Appropriate engineering controls**

: Systems under pressure should be regularly checked for leakages.
: Provide adequate general and local exhaust ventilation.
: Consider work permit system e.g. for maintenance activities.

LIQUEFIED PETROLEUM GAS (LPG)**AL623****SECTION 8. Exposure controls/personal protection (continued)**

- 8.2.2. Individual protection measures, e.g. personal protective equipment** : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered.
Wear safety glasses with side shields
Wear leather safety gloves and safety shoes when handling cylinders.
- 8.2.3. Environmental exposure controls** : None necessary.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

- Appearance**
- Physical state at 20°C / 101.3kPa : Gas.
 - Colour : Colourless.
 - Odour : Odourless.
 - Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.
 - pH value : Not applicable for gas-mixtures.
 - Molar mass [g/mol] : Not applicable for gases and gas-mixtures.
Not applicable for gases and gas-mixtures.
 - Melting point [°C] : Not applicable for gas-mixtures.
 - Boiling point [°C] : Not applicable for gas-mixtures.
 - Flash point [°C] : Not applicable for gas-mixtures.
 - Evaporation rate (ether=1) : Not applicable for gas-mixtures.
 - Flammability range [vol% in air] : Not applicable for gas-mixtures.
 - Vapour pressure [20°C] : Not applicable.
Not applicable.
 - Relative density, gas (air=1) : Lighter or similar to air.
 - Solubility in water [mg/l] : Not known, but considered to have low solubility.
 - Partition coefficient n-octanol/water : Not applicable for gas-mixtures.
Not applicable for gas-mixtures.
 - Viscosity at 20°C [mPa.s] : Not applicable.
 - Explosive Properties : Not applicable.

9.2. Other information

- Other data : None.

SECTION 10. Stability and reactivity**10.1. Reactivity**

- : No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

- : Stable under normal conditions.

10.3. Possibility of hazardous reactions

- : None.

10.4. Conditions to avoid

- : None.

10.5. Incompatible materials

- : None.

10.6. Hazardous decomposition products

LIQUEFIED PETROLEUM GAS (LPG)

AL623

SECTION 10. Stability and reactivity (continued)

: None.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	: No toxicological effects from this product.
Rat inhalation LC50 [ppm/4h]	: No data available.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information**12.1. Toxicity**

: No ecological damage caused by this product.

12.2. Persistence - degradability

: No data available.

12.3. Bioaccumulative potential

: No data available.

12.4. Mobility in soil

: No data available.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

12.6. Other adverse effects

Effect on ozone layer	: None.
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

: May be vented to atmosphere.
Do not discharge into any place where its accumulation could be dangerous.
Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods
Contact supplier if guidance is required.

13.2. Additional information

: None.



LIQUEFIED PETROLEUM GAS (LPG)

AL623

SECTION 14. Transport information

UN number : 1075

Labelling ADR, IMDG, IATA



: 2.1 : flammable gas.

Land transport (ADR/RID)

H.I. nr : 23

UN proper shipping name : PETROLEUM GASES, LIQUEFIED

Transport hazard class(es) : 2

Classification code : 2 F

Packing Instruction(s) : P200

Tunnel Restriction : B/D Tank carriage: Passage forbidden through tunnels of category B, C, D

HAZCHEM - Emergency Action Code : 2YE

2 = Fine water spray.

Y = Risk of violent reaction or explosion. Recommended personal protective equipment : Full fire kit and breathing apparatus. Appropriate measures : contain.

E = There may be a public safety hazard outside the immediate area of the incident, and that the following actions should be considered :

1. People should be warned to stay indoors with all doors and windows closed, preferably in rooms upstairs and facing away from the incident. Ignition sources should be eliminated and any ventilation stopped.

2. Effects may spread beyond the immediate vicinity. All non-essential personnel should be instructed to move at least 250 metres away from the incident.

3. Police and fire brigade incident commanders should consult each other and with a product expert, or with a source of product expertise.

4. The possible need for subsequent evacuation should be considered, but it should be remembered that in most cases it will be safer to remain in a building than to evacuate.

Sea transport (IMDG)

Proper shipping name : PETROLEUM GASES, LIQUEFIED

Class : 2.1

Emergency Schedule (EmS) - Fire : F-D

Emergency Schedule (EmS) - Spillage : S-U

Packing instruction : P200

Air transport (ICAO-TI / IATA-DGR)

Proper shipping name (IATA) : PETROLEUM GASES, LIQUEFIED

Class : 2.1

Passenger and Cargo Aircraft : DO NOT LOAD IN PASSENGER AIRCRAFT.

Cargo Aircraft only : Allowed.

Packing instruction - Cargo Aircraft only : 200

Special precautions for user

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers :

- Ensure there is adequate ventilation.

- Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.



MATERIAL SAFETY DATA SHEET

Page : 8

Revised edition no : 3

Date : 7 / 11 / 2012

Supersedes : 25 / 9 / 2012

LIQUEFIED PETROLEUM GAS (LPG)

AL623

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Seveso directive 96/82/EC : Not covered.

National legislation

: Ensure all national/local regulations are observed.

15.2. Chemical Safety Assessment

: A CSA does not need to be carried out for this product.

SECTION 16. Other information

- Indication of changes** : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010
- Training advice** : Receptacle under pressure.
Receptacle under pressure.
- List of full text of R-phrases in section 3.** : R12 : Extremely flammable.
- List of full text of H-statements in section 3.** : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
- Further information** : Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.
This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
- DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

The contents and format of this SDS are in accordance with EC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document